## HOW TO CHOOSE YOUR HAMMER

		CHIPPER		PICK HAMMER		BREAKER						
		P5	P7	P9	P13	AIRGO	BB15	BB20	BB25	BB27	BB32	BB40
MATERIALS	AGGLO	~	~	~	~							
	BRICK	~	~	✓	~							
	CEMENT	~	~	✓	~	~	~	~	~	~	~	~
	ASPHALT					✓	~	~	✓	~	~	~
	STONE					✓	~	~	✓	~	~	~
TYPE OF WORKS	PATCH	~	✓	~	~							
	DEMOLITION			~	<b>~</b>	✓	~	~	✓	✓	✓	~
	AIR CONSUMPTION I/min - cfm	500 - 17,7	900 - 31,8	1 000 - 35,3	1200 - 42,4	1200 - 42,4	1200 - 42,4	1100 - 38,8	1200 - 42,4	1200 - 42,4	1200 - 42,4	1600 - 56,5
	CADENCE bpm	2800	2200	1800	1500	1000	1300	1300	1300	1200	1150	1100
TECHNICAL SPECIFICATIONS	SOUND LEVEL dB R=1m	97	97	97	97	99	98	99	99	100	100	104
	VIBRATION LEVEL m/s	<5	<5	<8	<10	<5	-	<5	<5	<10	<10	<12
	WEIGHT kg	5 kg	7 kg	9 kg	13 kg	21 kg	15 kg	20 kg	25 kg	27 kg	32 kg	40 kg



The jackhammer can be used to carry out a wide variety of jobs on site, from simple surface renovation to heavy demolition. The use of MAC3 breakers can be adapted to all situations.

With our complete line of pneumatic breakers, you are guaranteed to increase productivity on the job site while reducing exposure to vibration, noise and dust.

Our products offer superior performance to corded, battery-powered models with the added bonus of productivity.

Choosing the right breaker for the application increases productivity on the job site and reduces user fatigue.

OUR BREAKERS AND DEMOLITION HAMMERS ARE DESIGNED TO WITHSTAND THE TOUGHEST JOB SITE CONDITIONS.

